

Express Mail Label No. EV 318 174 124 US

Date of Mailing August 27, 2003

PATENT
Case No. **GP-303940**
(2760/126)

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE
APPLICATION FOR UNITED STATES LETTERS PATENT

INVENTOR(S): UMA ARUN

TITLE: ALGORITHM FOR INTELLIGENT SPEECH
RECOGNITION

ATTORNEYS: ANTHONY LUKE SIMON, ESQ.
GENERAL MOTORS CORPORATION
LEGAL STAFF
MAIL CODE: 482-C23-B21
300 RENAISSANCE CENTER
P.O. BOX 300
DETROIT, MICHIGAN 48265-3000
(313) 665-4714

ALGORITHM FOR INTELLIGENT SPEECH RECOGNITION

5

FIELD OF THE INVENTION

In general, the invention relates to speech recognition systems. More specifically, the invention relates to a method for intelligent speech recognition.

BACKGROUND OF THE INVENTION

10

Telematic communication units (TCU's) such as cellular phones, person data assistants (PDA's), Global Positioning System (GPS) devices, and on-board Vehicle Communication Units (VCU's), used in conjunction with a Wide Area Network (WAN), such as a cellular telephone network or a satellite communication system, have made it possible for a person to send and receive voice communications, data transmissions, and facsimile messages from virtually anywhere on earth. Such communication can be initiated at the TCU when it is turned on, or by entering a phone number to be called, or in many cases, by speaking a voice command to an automatic speech recognition system (ASR), causing the TCU to automatically complete the process of dialing the number to be called.

20

A current problem with speech recognition systems is one of premature enunciation by users. Such users of speech recognition systems give voice commands to the speech recognition system before the system is ready to receive the command. A current speech recognition system, after its activation by a user, plays back a prompt stating that it is ready. A short time after the ready prompt, the speech recognition system begins a listening period during which it is able to receive and record commands. However, a considerable amount of users will begin saying commands before the speech recognition system has started the listening period. Such premature enunciators will usually hear a generic error response of "Slower Please" from the speech recognition

25

30

system, followed by the system replaying the ready prompt. For such users it becomes very annoying and time consuming to listen to the "Slower Please" error message all the time. Thus, there is a significant need for a method and
5 system for improving speech recognition for premature enunciation that overcomes the above disadvantages and shortcomings, as well as other disadvantages.

SUMMARY OF THE INVENTION

One aspect of the invention presents a method for a speech recognition
10 system to adjust to commands of premature enunciators. The method comprises activating the speech recognition system, informing the user that the speech recognition system is ready to receive speech input, and initiating a listening period. The method further comprises receiving input from a user before the system is ready to receive such input, identifying the user as a premature
15 enunciator, and adjusting the system to allow for earlier detection of user speech input.

Another aspect of the invention presents a computer readable medium for a speech recognition system to adjust to premature enunciators. The computer readable medium comprises computer readable code for activating the speech
20 recognition system, informing the user that the speech recognition system is ready to receive speech input, and initiating a listening period. The computer readable medium further comprises computer readable code for receiving input from a user before the system is ready to receive such input and identifying the user as a premature enunciator. The computer readable medium further
25 comprises computer readable code for adjusting the system to allow for earlier detection of user speech input.

Another aspect of the invention provides a system for speech recognition that adjusts to premature commands. The system comprises means for activating the speech recognition system, informing the user that the speech
5 recognition system is ready to receive speech input, and initiating a listening period. The system further comprises means for receiving input from a user before the system is ready to receive such input and identifying the user as a premature enunciator. The system further comprises means for adjusting the system to allow for earlier detection of user speech input.

10 The foregoing and other features and advantages of the invention will become further apparent from the following detailed description of the presently preferred embodiment, read in conjunction with the accompanying drawings. The detailed description and drawings are merely illustrative of the invention rather than limiting, the scope of the invention being defined by the appended
15 claims and equivalents thereof.

BRIEF DESCRIPTION OF THE FIGURES

FIG. 1 is a schematic diagram for one embodiment of a system for accessing a speech recognition system using a wireless communication system,
20 in accordance with the current invention; and

FIG. 2 is a flowchart outlining one embodiment of a method for a speech recognition system to adjust to premature enunciator commands utilizing the system of **FIG. 1** in accordance with the instant invention.

25

DETAILED DESCRIPTION OF THE PRESENTLY PREFERRED EMBODIMENTS

5 **FIG. 1** shows an illustration of one embodiment of a system for communicating with a mobile vehicle using a wireless communication system in accordance with the present invention, and is also referred to as a mobile vehicle communication system (MVCS) **100**. The mobile vehicle communication system **100** may contain one or more mobile vehicles (mobile vehicle communication unit, MVCU) **110**, one or more wireless carrier systems (wireless service providers) **120**, one or more communication networks **130**, one or more short message service centers **132**, one or more land networks **140**, and one or more call centers **150**. One embodiment of the call center **150** contains one or more switches **151**, one or more data transmission devices **152**, one or more
10 communication services managers **153**, one or more communication services databases **154**, one or more advisors **155**, one or more bus systems **156**, and one or more automatic speech recognition (ASR) units **157**.

 MVCU **110** includes a wireless vehicle communication device (module, MVCS module) such as an analog or digital phone with suitable hardware and
20 software for transmitting and receiving data communications. In one embodiment, MVCU **110** further includes a wireless modem for transmitting and receiving data. In another embodiment, MVCU **110** includes a digital signal processor with software and additional hardware to enable communications with the mobile vehicle and to perform other routine and requested services.

25 Additionally, MVCU **110** includes a global positioning system (GPS) unit capable of determining synchronized time and a geophysical location of the mobile vehicle. In operation, MVCU **110** sends to and receives radio transmissions from wireless carrier system **120**. MVCU **110** is also referred to as a mobile vehicle throughout the discussion below. In operation, MVCU **110** may
30 be implemented as a motor vehicle, a marine vehicle, or as an aircraft.

In a further embodiment, MVCU **110** contains an automatic speech recognition system (ASR) capable of communicating with the wireless vehicle communication device, and contains a speech recognition engine capable of word, phrase, or sentence recognition. An additional embodiment of the module provides the capacity of functioning as any part of, or as all of the above communication devices. In another embodiment of the invention, the module is capable of data storage, and/or data retrieval, and/or receiving, processing, and transmitting data queries.

In yet another embodiment, the MVCS module further includes an audio speaker, a synthesized voice output, an audio channel, or the like. In an example, a MVCS module is implemented, in addition to the receiver, as a set of headphones, the audio portion of a television, a display device, speakers, or the like.

Wireless carrier system **120** is a wireless communications carrier or a mobile telephone system and transmits to and receives signals from one or more MVCU **110**. In one example, the mobile telephone system is an analog mobile telephone system operating over a prescribed band nominally at 800 MHz. In another embodiment, the mobile telephone system is a digital mobile telephone system operating over a prescribed band nominally at 800 MHz, 900 MHz, 1900 MHz, or any suitable band capable of carrying mobile communications.

A further embodiment of the MVCS **100** provides the wireless carrier system **120** to be connected with communication network **130**. One example of the communication network **130** contains a mobile switching center and provides services from one or more wireless communications companies.

Another embodiment of the MVCS **100** allows for communication network **130** to be any suitable system or collection of systems for connecting wireless carrier system **120** to at least one mobile vehicle **110** or to a call center.

Communication network **130** includes one or more short message service centers **132**. Short message service center **132** is capable of prescribing alphanumeric short messages to and from mobile vehicles **110**, and includes .

5 message entry features, administrative controls, and message transmission capabilities. For one embodiment of the invention, the short message service center **132** includes one or more automated speech recognition (ASR) units. Another example of the short message service center **132** stores and buffers the

10 messages, and includes functional services (short message services) such as paging, text messaging and message waiting notification. An example of the short message services includes telematic services such as broadcast services, time-driven message delivery, autonomous message delivery, and database-driven information services. Another example of the short message services includes message management features, such as message priority levels,

15 service categories, expiration dates, cancellations, and status checks.

A public-switched telephone network is one example of the land network **140**, and contains at least one wired network, optical network, fiber network, wireless network, or any combination thereof. Another example of the land network **140** is in communication with an Internet protocol (IP) network. A further

20 example of the land network **140** connects the communication network **130** to a call center. Yet another example of the land network **140** connects a first wireless carrier system **120** with a second wireless carrier system **120**, and also connects wireless carrier system **120** to a communication node or call center **150** with the use of the communication network **130**. In another embodiment of the

25 invention, a communication system references all or part of the wireless carrier system **120**, communication network **130**, land network **140**, and short message service center **132**.

Call center **150** is a location where many calls can be received and serviced at the same time, or where many calls may be sent at the same time. Example call centers are telematic call centers, prescribing communications to and from mobile vehicles **110**, voice call centers, providing verbal communications between an advisor in the call center and a subscriber in a mobile vehicle, and voice activated call centers, providing verbal communications between an ASR unit and a subscriber in a mobile vehicle. The call center may contain any combination of hardware or software facilitating data transmissions between call center **150** and mobile vehicle **110**. A further embodiment of the invention provides that the call center contains any of the previously described functions.

One embodiment of the call center contains switch **151**. Switch **151** is connected to land network **140**, and receives a modem signal from an analog modem or from a digital modem. Switch **151** transmits voice or data transmission from the communication node. Another embodiment of switch **151** can receive voice or data transmissions from mobile vehicle **110** through wireless carrier system **120**, communication network **130**, and land network **140**, and can receive from or send data transmissions to data transmission device **152**. A further embodiment of switch **151** can receive from or send voice transmissions to advisor **155** via bus system **156**. Switch **151** can receive from or send voice transmissions to one or more automated speech recognition (ASR) units **157** via bus system **156**.

Data transmission device **152** sends or receives data from switch **151**. An example data transmission device **152** is an IP router or a modem. Data transmission device **152** transfers data to or from advisor **155**, one or more communication services managers **153**, one or more communication services databases **154**, one or more automated speech recognition (ASR) units **157**, and any other device connected to bus system **156**. Another example of data

30

transmission device **152** conveys information received from short message service center **132** in communication network **130** to communication services manager **153**.

5 The communication services manager **153** is connected to switch **151**, data transmission device **152**, and advisor **155** through bus system **156**. Another embodiment of the communication services manager **153** receives information from mobile vehicle **110** through wireless carrier system **120**, short message service center **132** in communication network **130**, land network **140**, and data
10 transmission device **152**. Additionally, an embodiment of communication services manager **153** sends information to mobile vehicle **110** through data transmission device **152**, land network **140**, communication network **130** and wireless carrier system **120**. Further embodiments of the communication services manager **153** send short message service messages via short message
15 service center **132** to the mobile vehicle, receive short message service replies from mobile vehicle **110** via short message service center **132**, send short message service requests to mobile vehicle **110**, and receive from or send voice transmissions to one or more automated speech recognition (ASR) units **157**.

 Communication services database **154** contains records on one or more
20 mobile vehicles **110**, with a portion of communication services database **154** dedicated to short message services. In an example, records in communication services database **154** include vehicle identification, location information, diagnostic information, status information, recent action information, and vehicle passenger (user, customer) and operator (user, customer) defined preset
25 conditions regarding mobile vehicle **110** and any of the communication services. Another embodiment of the invention requires that communication services database **154** provide information and other support to communication services manager **153** and automated speech recognition (ASR) units **157**, and to external VRE services.

30

Examples of advisor **155** are real advisors and virtual advisors. A real advisor is a human being in verbal communication with mobile communication device **110**. A virtual advisor is a synthesized voice interface responding to requests from mobile communication device **110**. Advisor **155** provides services to mobile communication device **110**, and can communicate with communication services manager **153**, automated speech recognition (ASR) units **157**, or any other device connected to bus system **156** or mobile communication device **110**. Another embodiment of the invention allows for the advisor **155** and ASR units **157** to be integrated as a single unit capable of any features described for either.

FIG. 2 is a flowchart outlining one embodiment of a method for a speech recognition system to adjust to premature enunciator commands in accordance with the present invention. The method begins at block **205**. A speech recognition system embedded in the MVCU receives an initiation sequence from the user, at block **210**, to activate the speech recognition system. This may be done by pressing a speech recognition activation button on the speech recognition system, or by turning the car's ignition to the on position. In one embodiment, the user presses the "voice" button to activate the system. In another embodiment, the speech recognition system turns on when the user starts the vehicle. The speech recognition system then acknowledges that it is ready to receive speech input at block **220**. This may be done by the speech recognition system playing back a recording prompt of "ready", or turning on a light indicator, or another audible feedback, including a beep.

Following a first predetermined time period, after the system gives the ready response, the speech recognition system begins listening for user speech input. In one embodiment, this first delay is 25-200 ms, but the first time delay may be any predetermined time delay. If the user begins speaking before the speech recognition system is ready to receive speech input, then the speech recognition system determines that the user has talked prematurely at block **230**. This occurs if the user speaks before the first time delay after the "ready"

5 playback has expired, or if the user speaks before the playback of “ready” is finished. The speech recognition system then outputs an error associated with a premature enunciator and advises the user at block **240** to begin speaking the command later. In one embodiment, this is done by the speech recognition system playing back a “Slower Please” response. The speech recognition system then checks at block **250** whether the error count, associated with the user talking too soon, exceeds a predetermined number. In the present embodiment, this predetermined number of errors is 3. If the error count is not exceeded then the speech recognition system returns to block **230** and again informs the user that it is ready. The user then again inputs the voice command and follows the sequence of blocks to block **250**. If the number of errors does exceed the predetermined number at block **250**, then the speech recognition system enters a premature enunciator mode and proceeds to block **260**. In premature enunciator mode, the ASR begins a second listening period at a second time. In one embodiment, the second time is shorter than the first delay. In one embodiment, the second listening period begins prior to the system finishing the “slower please” response. In the present embodiment, this interval is 50 to 100 ms before the “ready” prompt playback is finished. The premature enunciator user then gives the voice command again to the speech recognition system, at block **270**.

25 The speech recognition system now receives the full command, as a result of its earlier listening time, and filters unnecessary noise residue from the voice command at block **280**. In the present embodiment, this residue may be the entire or part of the overlaying “ready” playback prompt. Filtering the noise residue may be accomplished in any one of a number of ways, as is well known in the art. The speech recognition system then processes the filtered voice command at block **290** and plays back a response to the user’s command. The speech recognition system may process the command internally or send the command through the carrier system **120**. This type of response is known as the

30

“result of recognition.” The system then stops and waits for the next user command at block **295**. In one embodiment, the system remains in the premature enunciator mode until the speech recognition system is turned off. In
5 another embodiment, the speech recognition system resets the premature enunciator mode to its normal mode of operation with the regular listening period interval of 50 ms as soon as the first command is processed at block **295**. In another embodiment, the system may reset to a default mode from premature enunciator mode when the vehicle ignition is turned off. In another example, the
10 system remains in premature enunciator mode until specifically reset by a user regardless of ignition. If the reset is user controlled, means for resetting the system are provided. The means for resetting the system may comprise a reset button, or other system known to those of skill in the art.

The above-described methods and implementation for intelligent speech
15 detection and associated information are example methods and implementations. These methods and implementations illustrate one possible approach for providing detection of premature enunciators, and adjusting the speech recognition system in a meaningful way so as to improve customer satisfaction and service. The actual implementation may vary from the method discussed.
20 Moreover, various other improvements and modifications to this invention may occur to those skilled in the art, and those improvements and modifications will fall within the scope of this invention as set forth below.

The present invention may be embodied in other specific forms without departing from its spirit or essential characteristics. The described embodiments
25 are to be considered in all respects only as illustrative and not restrictive.